



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/673,605	09/29/2003	Kum Foo Leong	884.A68US1	2399
21186	7590	06/15/2005	EXAMINER	
SCHWEGMAN, LUNDBERG, WOESSNER & KLUTH, P.A. P.O. BOX 2938 MINNEAPOLIS, MN 55402-0938			PAREKH, NITIN	
			ART UNIT	PAPER NUMBER
			2811	

DATE MAILED: 06/15/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

AK

<b>Office Action Summary</b>	Application No.	Applicant(s)	
	10/673,605	LEONG ET AL.	
	Examiner	Art Unit	
	Nitin Parekh	2811	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 25 April 2005.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-19 and 28-39 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-19 and 28-39 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 09-29-03 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \* c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- \* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |   |   |
|---|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)                        | 4) <input type="checkbox"/> Interview Summary (PTO-413)                     |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)    | Paper No(s)/Mail Date. _____  |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| Paper No(s)/Mail Date _____   | 6) <input type="checkbox"/> Other: _____                                    |

## **DETAILED ACTION**

### ***Request for Continued Examination***

1. A request for continued examination (RCE) under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 04/25/05 has been entered. An action on the RCE follows.

### ***Claim Rejections - 35 USC § 112***

2. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

3. Claim 6 contains the trademark/trade name Kovar. Where a trademark or trade name is used in a claim as a limitation to identify or describe a particular material or product, the claim does not comply with the requirements of 35 U.S.C. 112, second paragraph. See *Ex parte Simpson*, 218 USPQ 1020 (Bd. App. 1982). The claim scope is uncertain since the trademark or trade name cannot be used properly to identify any particular material or product. A trademark or trade name is used to identify a source of goods, and not the goods themselves. Thus, a trademark or trade name does not identify or describe the goods associated with the trademark or trade name. In the present case, the trademark/trade name is used to identify/describe the source Carpenter Technology and, accordingly, the identification/description is indefinite.

***Claim Rejections - 35 USC § 103***

4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

5. Claims 1-5, 8, 9, 12-14, 16, 18, 19 and 31-40, insofar as being in compliance with 35 U.S.C. 112, are rejected under 35 U.S.C. 103(a) as being unpatentable over Marlin (US Pat. 6429046) in view of Paunovic et al. (US Pat. 5294486) and admitted prior art (APA).

A. Regarding claims 1-5, 8, 9, 12 and 13, Marlin et al. disclose a flip chip bumped device having a plurality of solder bumps/balls on respective under bump metal (UBM) pad structure (Fig. 1-6; Col. 1, lines 20-25; Col. 1, line 55- Col. 3, line 18) comprising:

- a flip chip substrate/FCS (see 102 in Fig. 5 and 6) including a first major/top surface and a second/bottom major surface

- the UBM pad structure including pads/array of pads being made of an electrically conductive/metal material (302/304/308 in Fig. 5 and 6) on a copper pad (see 104 in Fig. 5 and 6; Col. 1, line 60) and being positioned on the first/top surface, the UBM pad structure (302/304/308 in Fig. 5 and 6) comprising a plurality of layers including:
  - o a solderable oxidation/diffusion retarding layer (304 in Fig. 5; Col. 2, lines 33-36) made of a material such as nickel to retard the rate of oxidation/diffusion of species/electrically conductive material from the pad structure
  - o an adhesion/binding/non-wettable layer (302 in Fig. 5 and 6) for binding the oxidation retarding layer to the conductive material of the pad, the adhesion/binding/non-wettable layer including titanium (Ti) or titanium-tungsten (Col. 2, lines 5-15), and
  - o a solder support/receiving layer (308 in Fig. 5 and 6) such as gold (Col. 2, line 61) being placed on the oxidation/diffusion retarding layer
- the above UBM structure providing the layers/means to prevent diffusion of material into the copper pad and the chip, dissolving of the copper and that for adhering/binding the pad, and
- a solder bump/ball (310 in Fig. 5 and 6) being attached/formed on the copper pad, the solder including a tin (Sn) based lead-free solder (Col. 2, line 19)

(Fig. 5/6; Fig. 1-6; Col. 1-3).

Marlin fails to:

- a) explicitly teach the device having the pads having the solder ball being in a form of a ball grid array (BGA), and
- b) teach the diffusion retarding layer being functional as the layer for controlling out-diffusion of the electrically conductive material from the at least one pad.

a) APA teaches conventional flip chip device being in a conventional BGA configuration (see specification pages 1 and 2).

b) Paunovic et al. teach a prior art (see Col. 1, lines 50-65- prior art: US Pat. 4016050, Lesh et al.) disclosing a conventional diffusion barrier structure wherein a diffusion retarding layer such as nickel having a predetermine thickness is used to control/retard diffusion of copper from an underlying conductor/pad layer and to provide improved bonding (also see the prior art: Lesh et al, Col. 3, lines 23-37).

It would have been obvious to a person of ordinary skill in the art at the time invention was made to incorporate the elements a) and b) as taught by the APA and Paunovic et al. so that the improved diffusion barrier, solderability and interconnect reliability can be achieved in the APA and Marlin's device.

**B.** Regarding claim 1, using the diffusion retarding layer to prevent the out-diffusion during the solder reflow process do not distinguish over Marlin, Paunovic et al. and

APA, because only the final product/structure is relevant, not preventing the out-diffusion during "solder reflow process", "solder pre-heat ramp-up process" or "environmental/thermal cycling process". Note that a "product by process" claim is directed to the product per se, no matter how actually made, In re Hirao, 190 USPQ 15 at 17 (footnote 3). See also In re Brown, 173 USPQ 685; In re Luck, 177 USPQ 523; In re Fessmann, 180 USPQ 324; In re Avery, 186 USPQ 161; In re Wertheim, 191 USPQ 90 (209 USPQ 554 does not deal with this issue); and In re Marrosi et al., 218 USPQ 289, all of which make it clear that it is the patentability of the final product per se which must be determined in a "product by process" claim, and not the patentability of the process, and that an old or obvious product produced by a new method is not patentable as a product, whether claimed in "product by process" claims or not. Note that applicant has the burden of proof in such cases, as the above case law makes clear. See also MPEP 706.03(e).

Regarding claims 14, 16, 18, 19 and 31-40, Marlin, Paunovic et al. and APA teach substantially the entire claimed structure as applied to claim 1 above.

6. Claims 10 and 11, insofar as being in compliance with 35 U.S.C. 112, are rejected under 35 U.S.C. 103(a) as being unpatentable over Marlin (US Pat. 6429046), Paunovic et al. (US Pat. 5294486) and APA as applied to claim 1 above, and further in view of Andricacos et al. (US Pat. 6224690).

Regarding claims 10 and 11, Marlin, Paunovic et al. and APA teach substantially the entire claimed structure as applied to claim 1 above, except the binding layer having a thickness in a range of 80- 120 nm or 90-110 nm respectively.

Andricacos et al. teach a flip chip/BGA device having an UBM structure, the UBM structure including conventional adhesion/binding layers comprising titanium, chromium, etc., the adhesion/binding layer having a thickness of about 100 nm to provide the desired adhesion and barrier properties (Col. 4, lines 45-55).

It would have been obvious to a person of ordinary skill in the art at the time invention was made to incorporate the binding layer having a thickness in a range of 80-120 nm or 90-110 nm as taught by Andricacos et al. so that the binding/adhesion can be improved in Paunovic et al., APA and Marlin's device.

7. Claims 6, 7, 15 and 17, insofar as being in compliance with 35 U.S.C. 112, are rejected under 35 U.S.C. 103(a) as being unpatentable over Marlin (US Pat. 6429046), Paunovic et al. (US Pat. 5294486) and APA as applied to claims 1 and 14 above, and



further in view of Andricacos et al. (US Pat. 6224690) and Okamoto et al. (US Pat. 5521438).

Regarding claims 6 and 7, Marlin, Paunovic et al. and APA teach substantially the entire claimed structure as applied to claim 1 above, except the diffusion-retarding layer including Kovar or a composition 54Fe-29Ni-17Co respectively.

Andricacos et al. teach the flip chip/BGA device having a variety of configurations of the UBM structure including a configuration where a layer comprising nickel or a nickel alloy such as FeNi (see Fig. 2b) is used between the binding layer and solder receiving layer for a lead-free solder to provide the adhesion and to prevent further diffusion of an intermetallic (Col. 8, lines 1-37).

Okamoto et al. teach using soldered connections comprising terminals/electrodes made of conventional Fe-Ni based alloys including commercially available Kovar and low thermal expansion Kovar, such Fe-Ni-Co alloys having different wt.%/amount of Ni, Fe and Co (Col. 6, lines 65- Col. 8, line 65) to provide the desired joining strength, reduced thermal stress and improved reliability (Col. 6-12).

Furthermore, arriving at an optimum alloy composition from effective variables such as wt.% of various components/elements in the alloy composition involves routine skill in the art of chip packaging and interconnect technology to achieve the desired final properties in the bonding material such as bonding strength, adhesion, diffusion resistance, etc [see *In re Boesch*, 617 F.2d 272, 205 USPQ 215 (1980)].

It would have been obvious to a person of ordinary skill in the art at the time invention was made to incorporate the diffusion retarding layer including Kovar or a composition 54Fe-29Ni-17Co as taught by Andricacos et al. and Okamoto et al. so that the diffusion resistance and adhesion/bonding can be improved in Paunovic et al., APA and Marlin's device.

Regarding claims 15 and 17, Marlin, Paunovic et al., APA, Andricacos et al. and Okamoto et al. teach substantially the entire claimed structure as applied to claims 14 and 1 above.

8. Claims 28-30 are rejected under 35 U.S.C. 103(a) as being unpatentable over Marlin (US Pat. 6429046), Paunovic et al. (US Pat. 5294486) and APA and as applied to claim 1, and further in view of Andricacos et al. (US Pat. 6224690) and Shimokawa et al. (US Pat. 2002/0163085).

Regarding claims 28-30, Marlin, Paunovic et al. and APA teach substantially the entire claimed structure as applied to claims 1 above, except the pad including an intermetallic compound including Ni-Sn/Ni<sub>3</sub>Sn<sub>4</sub> and Ni-Fe.

Andricacos et al. teach the flip chip/BGA device having a variety of configurations of the UBM structure including a configuration where a layer comprising nickel or a nickel alloy such as FeNi (see Fig. 2b) is used between the binding layer and solder

receiving layer for a lead-free solder containing Sn to provide the adhesion and to prevent further diffusion of an intermetallic (Col. 8, lines 1-37).

Andricacos et al. further teach intermetallics such as Ni-Sn being formed at an interface when elements such as Ni and Sn are present in the pad layers and the solder (Col. 5, lines 25-32). Shimokawa et al. teach intermetallic compound such as Sn-Fe being formed at an interface when elements such as Sn and Fe are present in the solder alloy and the solder alloy (Col. 5, lines 25-32).

It would have been obvious to a person of ordinary skill in the art at the time invention was made to incorporate the pad including the intermetallic compound including Ni-Sn/Ni<sub>3</sub>Sn<sub>4</sub> and Ni-Fe as taught by Andricacos et al. and Shimokawa et al. so that the desired intermetallics remain adhered at the interface and further diffusion can be prevented in Paunovic et al., APA and Marlin's device.

### ***Response to Arguments***

9. Applicant's arguments filed on 04-25-05 have been fully considered but they are not persuasive.

A. Applicant contends that achieving the composition 54Fe-29Ni-17Co for the FeNi alloy is not truly the routine optimization and experimentation.

However, as explained above, Andricacos et al. teach the UBM structure including the configuration having the nickel alloy such as FeNi (see Fig. 2b) to provide the adhesion and to prevent further diffusion of an intermetallic (Col. 8, lines 1-37).

Art Unit: 2811

Okamoto et al. teach using soldered connections comprising terminals/electrodes made of conventional Fe-Ni based alloys including commercially available Kovar and a variety of Fe/Ni and Fe-Ni-Co alloys having different wt.%/amount of Ni, Fe and Co (Col. 6, lines 65- Col. 8, line 65) to provide the desired joining strength, reduced thermal stress and improved reliability (Col. 6-12). It would have been obvious to a person of ordinary skill in the art at the time invention was made to arrive at FeNiCo composition of 54Fe-29Ni-17Co, since it has been held that discovering an optimum value of a result effective variable involves only routine skill in the art (*In re Boesch*, 617 F.2d 272, 205 USPQ 215 (1980)).

B. Applicant contends that combining four references is an evidence of the application of hindsight by the examiner while using the invention as a roadmap.

However, the above argument is respectfully traversed.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Nitin Parekh whose telephone number is 571-272-1663. The examiner can normally be reached on 09:00AM-05:30PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Eddie Lee can be reached on 571-272-1732. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9318.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAN or Public PAG. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAG system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is 703-308-0956.

  
Nitin Parekh

PRIMARY EXAMINER

NP

TECHNOLOGY CENTER 2800

06-10-05